AMENDMENTS TO CLAIMS

1. (Currently amended) A method of recording information using a laser on a multilayer optical disk having a plurality of recording layers, the plurality of recording layers including a first recording layer and a second recording layer, the second recording layer being a recording layer adjacent the first recording layer, the first recording layer having a first test writing area to be used for calibration of write power and the second recording layer having a second test writing area to be used for calibration of write power, wherein a first region of the first test writing area is superposed with a second region of the second test writing area when considered in the direction in which the laser is arranged to irradiate, the method comprising:

if the second region of the second test writing area is unrecorded, recording data in the second region of the second test writing area, thereby converting the second region of the second test writing area into a recorded state;

once the second region of the second test writing area has been converted into a recorded state, performing test writing in the first region of the first test writing area; and

wherein before performing the test writing in the first region of the first test writing area, if the first region of the first test writing area is unrecorded, the method comprises: recording data in the first region of the first test writing area, thereby converting the first region of the first test writing area into a recorded state, and then clearing the first region of the first test writing area; and wherein the clearing of the first region of the first test writing area comprises performing

wherein the clearing of the first region of the first test writing area comprises performing an erasure operation to make the first region unrecorded.

- (Currently amended) A method according to Claim 1 or Claim 6, wherein the second
 recording layer is the next recording layer with respect to the first recording layer in the direction in
 which the laser is arranged to irradiate.
 - 3. (Canceled)

Application No. 10/582,481 Docket No. R2184.0506/P506

4. (Currently amended) A method according to any one of Claims 1 to 3 Claim 6, wherein before performing the test writing in the first region of the first test writing area, if the first region of the first test writing area is unrecorded, the method comprises: recording data in the first region of the first test writing area, thereby converting the first region of the first test writing area into a recorded state; and then clearing the first region of the first test writing area.

5. (Canceled)

6. (Currently amended) A method of recording information using a laser on a multilayer optical disk having a plurality of recording layers, the plurality of recording layers including a first recording layer and a second recording layer, the second recording layer being a recording layer adjacent the first recording layer, the first recording layer having a first test writing area to be used for calibration of write power and the second recording layer having a second test writing area to be used for calibration of write power, wherein a first region of the first test writing area is superposed with a second region of the second test writing area when considered in the direction in which the laser is arranged to irradiate, the method comprising:

if the second region of the second test writing area is unrecorded, recording data in the second region of the second test writing area, thereby converting the second region of the second test writing area into a recorded state:

once the second region of the second test writing area has been converted into a recorded state, performing test writing in the first region of the first test writing area; and

wherein, before performing the test writing in the first region of the first test writing area, the method comprises clearing the first region of the first test writing area; and

A method according to Claim 4 or Claim 5; wherein the clearing of the first region of the first test writing area comprises performing an erasure operation to make the first region unrecorded.

 (Currently amended) A method according to any one of Claims Claim 1 to 4 or Claim 6, wherein for the first region of the first test writing area, or the second region of the second Application No. 10/582,481 Docket No. R2184.0506/P506

test writing area, or the third region of the third test writing area; the respective step of recording data in the region thereby converting the region into a recorded state comprises performing an operation to make the region logically zero.

 (Currently amended) Apparatus arranged to record information to a multilayer optical disk having a plurality of recording layers using a laser, the plurality of recording layers including a first recording layer and a second recording layer,

the second recording layer being a recording layer adjacent the first recording layer, the first recording layer having a first test writing area to be used for calibration of write power and the second recording layer having a second test writing area to be used for calibration of write power, wherein a first region of the first test writing area is superposed with a second region of the second test writing area when considered in the direction in which the laser is arranged to irradiate, wherein

if the second region of the second test writing area is unrecorded, the apparatus is arranged to record data in the second region of the second test writing area, thereby converting the second region of the second test writing area into a recorded state;

once the second region of the second test writing area has been converted into a recorded state, the apparatus is arranged to perform test writing in the first region of the first test writing area; and

wherein, before performing the test writing in the first region of the first test writing area, the apparatus is arranged to clear the first region of the first test writing area; and

wherein the clearing of the first region of the first test writing area comprises performing an erasure operation to make the first region unrecorded.

 (Original) Apparatus according to Claim 8, wherein the second recording layer is the next recording layer with respect to the first recording layer in the direction in which the laser is arranged to irradiate.

10. (Canceled)

11. (Currently amended) Apparatus according to any one of Claims Claim 8 to 10 or Claim 9, wherein before performing the test writing in the first region of the first test writing area, if the first region of the first test writing area is unrecorded, the apparatus is arranged to: record data in the first region of the first test writing area, thereby converting the first region of the first test writing area into a recorded state; and then to clear the first region of the first test writing area.

12-13. (Canceled)

14. (Currently amended) Apparatus according to any one of Claims Claim 8 to 11 or Claim 9, wherein for the first region of the first test writing area, or the second region of the second test writing area, or the third region of the third test writing area, the apparatus is arranged such that the respective recording of data in the region thereby converting the region into a recorded state comprises performing an operation to make the region logically zero.

15-30. (Canceled)